



| REVISIONS |   |          |         |          |
|-----------|---|----------|---------|----------|
| REV       | DESCRIPTION   | DATE     | INITIAL | APPROVED |
| A         | UPDATED TITLEBLOCK & REVISION BLOCK, SEPARATED PARTS AND ADDED PAGE 2, CH'D TOOL NO. TO RB23006785. | 6/3/09   | RJC     | RW       |
| B         | CH'D BOM B/O INFO -1 & -2, ADDED -2 OPTIONAL CENTER NOTE PER G.E.                                   | 10/25/11 | RJC     | RW       |




|   |   |  |
|---|---|--|
| <div> <div>RB</div> <div>RED BARN MACHINE</div> </div>  |   |  |
| <div> <div>TITLE</div> <div>INST. TOOL - O-RING SPUR ADAPT. GEAR</div> </div>   |   |  |
| <div> <div>DWG NO.</div> <div>RB23006785</div> </div>   | <div> <div>REV</div> <div>B</div> </div>        |  |
| <div> <div> <div>UNLESS OTHERWISE SPECIFIED</div> <div>DIMENSIONS ARE IN INCHES</div> <div>TOLERANCES ON:</div> <div> <div>DECIMALS</div> <div>.XXX ± .005</div> <div>.XX ± .01</div> <div>.X ± .1</div> </div> <div> <div>FRACTIONS ± 1/32</div> <div>ANGLES ± 5°</div> </div> </div> </div> |   | <div> <div>DRAWN BY:</div> <div>PERRITT</div> </div>   |
| <div> <div>APPROVED</div> <div><i>D Weil</i></div> </div>   |   | <div> <div>HEAT TREAT</div> <div>FINISH</div> <div>SPEC</div> </div>                               |
| <div> <div>UNLESS OTHERWISE SPECIFIED</div> <div>1. BREAK ALL SHARP EDGES</div> <div>.015 x 45° PR .015 R</div> <div>2. DIMENSIONAL LIMITS APPLY AFTER PLATING</div> </div>   |   | <div> <div>USED ON MODEL</div> <div>250-C288, C280, C30, C30L, C30M, C30P, C30R, C30S</div> </div> |
| <div> <div>SCALE</div> <div>NTS</div> </div>  | <div> <div>DATE</div> <div>4-27-07</div> </div> | <div> <div>SHEET</div> <div>1 of 3</div> </div>  |


| ASSY QTY | ASSY QTY | B/O | PART # | UNIT QTY | DESCRIPTION | MATERIAL     | B/O INFORMATION OR SPECIFICATIONS | Pg. |
|----------|----------|-----|--------|----------|-------------|--------------|-----------------------------------|-----|
|          |          |     | -1     | 1        | RECIEVER    | STRESS PROOF | Ø1-1/8 x 2-5/16                   | 1   |
|          |          |     | -2     | 1        | SHAFT       | STRESS PROOF | Ø1 x 5                            | 2   |
|          |          |     |        |          |             |              |                                   |     |
|          | ASSY #   |     |        |          |             |              |                                   |     |

| REVISIONS |   |        |         |          |
|-----------|---|--------|---------|----------|
| REV       | DESCRIPTION   | DATE   | INITIAL | APPROVED |
| A         | UPDATED TITLEBLOCK & REVISION BLOCK, SEPARATED PARTS AND ADDED PAGE 2, CH'D TOOL NO. TO RB23006785. | 6/3/09 | RJC     | -        |



|  |   |
|--|---|
|  <b>RED BARN MACHINE</b>  |   |
| <b>TITLE</b><br>INST. TOOL - Ø-RING SPUR ADAPT. GEAR   |   |
| <b>DWG NO.</b><br>RB23006785-1   | <b>REV</b><br>B   |
| UNLESS OTHERWISE SPECIFIED<br>DIMENSIONS ARE IN INCHES<br>TOLERANCES ON:<br>DECIMALS<br>.XXX ± .005<br>.XX ± .01<br>.X ± .1<br>FRACTIONS ± 1/32<br>ANGLES ± 5° | <b>DRAWN BY:</b> PERRITT<br><b>APPROVED</b> <i>D Weil</i><br><b>HEAT TREAT</b><br><b>FINISH SPEC</b> BLACK OXIDE<br>USED ON MODEL |
| UNLESS OTHERWISE SPECIFIED<br>1. BREAK ALL SHARP EDGES<br>.015 x 45° PR .015 R<br>2. DIMENSIONAL LIMITS APPLY AFTER PLATING                                    | 250-C288, C280, C30, C30L,<br>C30M, C30P, C30R, C30S  |
| <b>SCALE</b> NTS   | <b>DATE</b> 4-27-07 <b>SHEET</b> 2 of 3   |

| REVISIONS |   |          |         |          |
|-----------|---|----------|---------|----------|
| REV       | DESCRIPTION   | DATE     | INITIAL | APPROVED |
| A         | UPDATED TITLEBLOCK & REVISION BLOCK, SEPARATED PARTS AND ADDED PAGE 2, CH'D TOOL NO. TO RB23006785. | 6/3/09   | RJC     | -        |
| B         | ADDED -2 OPTIONAL CENTER NOTE PER G.E.  | 10/25/11 | RJC     | RW       |



-2  
SHAFT

|   |  |
|---|--|
| RED BARN MACHINE  |  |
| TITLE INST. TOOL - O-RING SPUR ADAPT. GEAR  |  |
| DWG NO. RB23006785-2  | REV B  |
| UNLESS OTHERWISE SPECIFIED<br>DIMENSIONS ARE IN INCHES<br>TOLERANCES ON:<br>DECIMALS<br>.XXX ± .005<br>.XX ± .01<br>.X ± .1 | DRAWN BY: PERRITT<br>APPROVED: <i>D Weil</i><br>HEAT TREAT<br>FINISH BLACK OXIDE<br>SPEC USED ON MODEL<br>250-C288, C280, C30, C30L,<br>C30M, C30P, C30R, C30S |
| UNLESS OTHERWISE SPECIFIED<br>1. BREAK ALL SHARP EDGES<br>.015 x 45° PR .015 R<br>2. DIMENSIONAL LIMITS APPLY AFTER PLATING | SCALE NTS<br>DATE 4-27-07<br>SHEET 3 of 3  |

NOT APPROVED FOR PRODUCTION

| REVISIONS |             |      |          |
|-----------|-------------|------|----------|
| REV       | DESCRIPTION | DATE | APPROVED |
|           |             |      |          |

| PART # | QTY | DESCRIPTION      |
|--------|-----|------------------|
| -1     | 1   | 41L40 Ø5/8 x 3/4 |
|        |     |                  |

| USED ON MODEL |
|---------------|
| ?             |
|               |
|               |
|               |

|  |                  |
|--|------------------|
| DRAWN BY:  | WP               |
| APPROVED   |                  |
| HEAT TREAT   |                  |
| FINISH SPEC  | BLACK OXIDE      |
| UNLESS OTHERWISE SPECIFIED<br>DIMENSIONS ARE IN INCHES |                  |
| TOLERANCES ON:   |                  |
| DECIMALS   |                  |
| .XXX ± .005  | FRACTIONS ± 1/32 |
| .XX ± .01  | ANGLES ± 5°      |
| .X ± .1  |                  |
| UNLESS OTHERWISE SPECIFIED                             |                  |
| 1. BREAK ALL SHARP EDGES                               |                  |
| .015 x 45° PR .015 R                                   |                  |
| 2. DIMENSIONAL LIMITS APPLY AFTER PLATING              |                  |

|                     |         |
|---------------------|---------|
| RB RED BARN MACHINE |         |
| TITLE               |         |
| PART #              |         |
| DWG NO.             |         |
| SCALE               | NTS     |
| DATE                | 7-14-06 |
| SHEET               | 1 of 1  |

NOT APPROVED FOR PRODUCTION

| REVISIONS |             |      |          |
|-----------|-------------|------|----------|
| REV       | DESCRIPTION | DATE | APPROVED |
|           |             |      |          |

| PART # | QTY | DESCRIPTION           |
|--------|-----|-----------------------|
| -1     | 1   | 4140 3/16 x 1 1/2 x 4 |
|        |     |                       |

|  |   |                     |                           |
|--|---|---------------------|---------------------------|
| USED ON MODEL<br>?<br><br><br><br><br> | DRAWN BY: WP  | RB RED BARN MACHINE |                           |
|  | CHECKED   | TITLE               |                           |
|  | HEAT TREAT FINISH SPEC  | TITLE               |                           |
|  | UNLESS OTHERWISE SPECIFIED<br>DIMENSIONS ARE IN INCHES<br>TOLERANCES ON:<br>DECIMALS<br>.XXX ± .005<br>.XX ± .01<br>.X ± .1 | DWG NO. PART #      |                           |
|  | UNLESS OTHERWISE SPECIFIED<br>1. BREAK ALL SHARP EDGES .015 x 45° PR .015 R<br>2. DIMENSIONAL LIMITS APPLY AFTER PLATING    | SCALE NTS           | DATE 7-14-06 SHEET 1 of 1 |